



Classic Flatdeck with Duals - Available at Tucson Trailer Company

Trailers



Available Lengths:

- 20' 30' 40'
- 22' 32'
- 24' 34'
- 25' 35'
- 26' 36'
- 28' 38'

Standard Features

- 22,400 lb. G.V.W.R.
- 10,000 lb. x 2 G.A.W.R.
- 2 5/16" Gooseneck Ball Coupler (25,000 lb.)
- Safety Chains
- 2 - Drop Leg Jacks (10,000 lb.)
- 2 - Oil Bath Brake Axles (10,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 8 - 16" Grey Dual Wheels w/ 8 on 6.5" Bolt Pattern
- 8 - 16" 235/80R16 Radial Tires (3,097 lb.)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Side Steps on Both Sides
- Front Toolbox (GN Only)
- 8' Ramps w/ Holders
- 12" x 14 lb. I-Beam Main Frame, Riser & Neck
- 3" Channel Crossmembers 16" on Center
- 2" Treated Pine Lumber Deck
- 102" Wide Deck
- DOT Approved Flushmount Lifetime LED Lights
- Amber Side Turn Flashers
- Sealed Wire Harness
- Sand Blasted, Acid Washed, Powder Coated

Notes:

- 25' and up includes 19 lb. I-Beam Frame, Riser & Neck
- Pintlehooks must upgrade to 19 lb. I-Beam

Available Options

* Denotes Standard

Coupler Options

- GN 2 5/16" Round (25,000 lb.) ***
- BP 2 5/16" Adjustable (25,000 lb.)
- GN 2 5/16" Round (30,000 lb.)
- GN Load-Leveling 2 5/16" Square (30,000 lb.)
- 3" Pintle Eye - Face-mount (36,000 lb.)
- GN 2 5/16" Square (30,000 lb.)
- GN 2 5/16" Square (25,000 lb.)

Axle Options

Tail Options

- Straight Deck w/ 8' Slide-in Ramps ***
- 5' Dovetail w/ 5' Slide-in Ramps
- 5' Dovetail w/ 2 Flip-over Ramps
- 5' Split Pop-up Dove w/ 5' Slide-in Ramps
- 5' Center Pop-up Dove w/ 2 Flip-over Ramps
- 5' Dovetail w/ 3 Flip-over Ramps

Color Options

- Black Powdercoat ***

- (2) 10,000# Air (may affect Ramp Holders) / Spring
- (2) 10,000# Elec / Spring ***
- (2) 10,000# Elec / Torsion
- (2) 10,000# Elec/Hyd Disk / Spring
- (3) 10,000# Air (may affect Ramp Holders) / Spring
- (3) 10,000# Elec / Spring
- (3) 10,000# Elec / Torsion
- (3) 10,000# Elec/Hyd Disk / Spring
- (2) 10,000# Elec/Spring w/ Single 17.5 Tires Elec / Spring
- (2) 10,000# Elec/Spring w/ Single 17.5 Tires Elec / Torsion
- (3) 10,000# Elec/Spring w/ Single 17.5 Tires Elec / Spring
- (2) 10k Dexter Axles Elec / Spring
- (2) 12,000# Air (may affect Ramp Holders) / Spring
- (2) 12,000# Elec / Spring
- (2) 12,000# Elec/Hyd Disk / Spring
- (3) 12,000# Air (may affect Ramp Holders) / Spring
- (3) 12,000# Elec / Spring
- (3) 12,000# Elec/Hyd Disk / Spring
- (2) 12,000# 14ply Tires Air (may affect Ramp Holders) / Spring
- (2) 12,000# 14ply Tires Elec / Spring
- (2) 12,000# 14ply Tires Elec/Hyd Disk / Spring
- (3) 12,000# 14ply Tires Air (may affect Ramp Holders) / Spring
- (3) 12,000# 14ply Tires Elec / Spring
- (3) 12,000# 14ply Tires Elec/Hyd Disk / Spring
- (2) 12k Dexter Axles Elec / Spring
- (2) 16000# 215/75R17.5 Tires Air (may affect Ramp Holders) / Spring
- (2) 16000# 215/75R17.5 Tires Elec / Spring

- Equipment Yellow Powdercoat
- Grey Powdercoat
- Red Powdercoat
- White Powdercoat

Other Options

- Hutch suspension H9700-Underslung Tandem Axle
- AL-KO Axles
- Hutch suspension H9700-Underslung Triple Axle
- Plate for Winch
- Spare Tire Mount
- 6" Taller GN Riser
- Douglas Fir Lumber
- " Diamond Plate Steel Floor
- Under Frame Tie Down Flat
- 19 lb. I-Beam Main Frame, Riser & Neck
- 22 lb. I-Beam Main Frame, Riser & Neck
- 12"oc Crossmembers
- 1 Pair D-Rings
- Rough Oak Floor
- Weld-On Strap Ratchets (2)
- Hydraulic Jacks (12,000 lb.) Incl. Front Toolbox
- Receiver Hitch
- 4" Ratchets every 4ft w/ Slide Track
- 6" Axle Spread (Longer Equalizer)
- 72" Axle Spread
- Steel Floor & 4 D-Rings (Cut Fenders)
- Front Toolbox (PH Only)
- Frame Bridging
- Diamond Plate Ramp Bottoms
- Torque Tube
- Deck on the Neck 8x8 ft
- Side-mount Toolbox
- Winch 12VDC (12,000 lb.) Incl. Front Toolbox
- 2-speed Jacks (12,000 lb.)
- HD Semi Trailer 2x Jacks (25,000 lb.) No Frt T/box
- Ramp Support Arms