



Trailers

PJ Trailers - Disaster Relief Trailer - Available from Tucson Trailer Company



Available Lengths:

21'

Standard Features

- 22,400 lb. G.V.W.R.
- 10,000 lb. x 2 G.A.W.R.
- 2 5/16" Gooseneck Ball Coupler (25,000 lb.)
- Safety Chains
- 2 - Drop Leg Jacks (10,000 lb.)
- 2 - Oil Bath Brake Axles (10,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 8 - 16" Grey Dual Wheels w/ 8 on 6.5" Bolt Pattern
- 8 - 16" 235/80R16 Radial Tires (3,097 lb.)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Ladder on Right Side
- Toolbox
- 2 - Way Gate (Barn Doors & Spread Gate)
- 80" Ramps w/ Holders
- 4 Flushmount D-Rings
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- 10 Ton Scissor Lift
- Control
- 12" x 19 lb. I-Beam Main Frame, Riser & Neck
- 2x6" Tubing Deck Frame
- 3" Channel Crossmembers 16" on Center
- 12ga Steel Bed
- 96" Wide Bed
- 12ga. Steel Sides
- 48/24" Solid/Expanded Metal Removable Sides
- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness
- Sand Blasted, Acid Washed, Powder Coated

Available Options

* Denotes Standard

Coupler Options

Tail Options

- GN 2 5/16" Square (25,000 lb.) ***
- GN 2 5/16" Round (30,000 lb.)
- GN Load-Leveling 2 5/16" Square (30,000 lb.)
- 3" Pintle Eye - Face-mount (36,000 lb.)
- GN 2 5/16" Square (30,000 lb.)
- GN 2 5/16" Round (25,000 lb.)

Axle Options

- (2) 10,000# Air (may affect Ramp Holders) / Spring
- (2) 10,000# Elec / Spring ***
- (2) 10,000# Elec / Torsion
- (2) 10,000# Elec/Hyd Disk / Spring
- (2) 12,000# Air (may affect Ramp Holders) / Spring
- (2) 12,000# Elec / Spring
- (2) 12,000# Elec/Hyd Disk / Spring

- Barn Doors ***

Color Options

- Black Powdercoat ***
- Equipment Yellow Powdercoat
- Grey Powdercoat
- Red Powdercoat
- White Powdercoat

Other Options

- AL-KO Axles 10k
- Dexter Axles 10k
- 6" Taller GN Riser
- 12"oc Crossmembers
- Hydraulic Jacks (12,000 lb.) Incl. Front Toolbox
- Winch 12VDC (12,000 lb.) Incl. Front Toolbox
- 2-speed Jacks (12,000 lb.)
- HD Semi Trailer 2x Jacks (25,000 lb.) No Frt T/box